

ACCU LUNG

Portable Precision Test Lung

Technical Data



The ACCU LUNG Precision Test Lung is a lung simulator that presents a specific load comprised of user-selectable compliance and resistance for the purpose of evaluating ventilator performance according to clinical expectation and manufacturers' specification. It is a portable unit that can be hung from a cart, the ventilator itself, or hand-held, thus presenting a zero footprint.

Key features

- Small, lightweight and portable
- User-selectable compliance and resistance settings
- Calibrated accuracy for both resistance and compliance
- Complies with IEC standard for breathing-circuit connection
- Certified test lung for test system traceability to standards

Specifications

Environmental parameters	
Operating temperature	10 °C to 40 °C (50 °F to 104 °F)
Storage temperature	0 °C to 50 °C (-32 °F to 122 °F)
Performance characteristics	
Static compliance	C50 0.5 l/kPa ± 10 % at 500 ml tidal volume
	C20 0.2 l/kPa ± 10 % at 500 ml tidal volume
	C10 0.1 l/kPa ± 10 % at 300 ml tidal volume
Resistance	Parabolic (orifice) resistor pressure drops selected from ASTM F1100 (K values), for inspiratory flows at 2, 1, and 0.5 l/s, respectively
	Rp5 K 2.70 ± 20 % (equivalent orifice size = 8.48 mm) pressure drop 10.80 cmH ₂ O at 2 l/s
	Rp20 K 17.61 ± 20 % (equivalent orifice size = 5.31 mm) pressure drop 17.61 cmH ₂ O at 1 l/s
	Rp50 K 108.70 ± 20 % (equivalent orifice size = 3.37 mm) pressure drop 27.20 cmH ₂ O at 0.5 l/s
Physical characteristics	
Ventilator circuit connection	ISO 22 mm female
Warranty specifications	15 month extended warranty on all parts and labor with the following limitations: a) All rubber parts (including bellows made from Hypalon®) are warranted to be free from defects at the time of delivery b) Springs are considered limited lifecycle parts and are expected to survive 1 x 10 ⁶ cycles
Dimensions (LxWxH)	27.9 cm x 21.6 cm x 10.2 cm (11 in x 8.5 in x 4 in)
Weight	1.8 kg (4 lb)

Distribuido por: **celyon técnica, S.L.**
Pg. de les Torres, 100 Local 6
08191-RUBI (Barcelona)
Tel.: 936 999 001
Fax.: 935 883 687
info@celyontecnica.com
www.celyontecnica.com

Ordering information

Model numbers/descriptions

ACCU LUNG ACCU LUNG Precision Test Lung

Standard accessories

Instructions Operators Manual

ACCU LUNG CASE Soft-Sided Carrying Case

About Fluke Biomedical

Fluke Biomedical is the world's leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance. Highly credentialed and equipped with a NVLAP Lab Code 200566-6 accredited laboratory, Fluke Biomedical also offers the best in quality and customer service for all your equipment calibration needs.

Today, biomedical personnel must meet the increasing regulatory pressures, higher quality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today's challenges.

Fluke Biomedical Regulatory Commitment

As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 certified and our products are:

- CE Certified, where required
- NIST Traceable and Calibrated
- UL, CSA, ETL Certified, where required
- NRC Compliant, where required

Fluke Biomedical.

Better products. More choices. One company.

Fluke Biomedical

6045 Cochran Road
Cleveland, OH 44139-3303 U.S.A.

Fluke Biomedical Europe

Science Park Eindhoven 5110
5692EC Son, The Netherlands

For more information, contact us:

In the U.S.A. (800) 850-4608 or
Fax (440) 349-2307
In Europe/M-East/Africa +31 40 267 5435 or
Fax +31 40 267 5436
From other countries +1 (440) 248-9300 or
Fax +1 (440) 349-2307
Email: sales@flukebiomedical.com
Web access: www.flukebiomedical.com

©2010 Fluke Biomedical. Specifications subject to change without notice. All OEM company trademarks are implied. Printed in U.S.A. 3/2010 37770189A D-EN-N

Modification of this document is not permitted without written permission from Fluke Corporation.